


A Practical Homeowner's Guide to Understanding, Maintaining, and Making Informed Decisions

First Coast Heating & Air · Fictional demonstration publication · Jacksonville, Florida

Welcome

A practical homeowner's guide to understanding, maintaining, and making informed decisions about residential heating and air conditioning in Northeast Florida.

This guide is general educational information. It is not a repair manual, diagnosis, or substitute for manufacturer instructions or advice from a qualified HVAC professional. First Coast Heating & Air is a fictional demonstration brand.

Contents

01 — Your Home’s Comfort System: The Big Picture

02 — Why Jacksonville Homes Work Hard to Stay Cool

03 — How to Choose and Use Your Thermostat

04 — Air Filters: A Small Part with a Big Job

05 — Outdoor Unit Care and Clear Airflow

06 — Ductwork: The Hidden Part of Home Comfort

07 — Why Some Rooms Are Too Hot or Too Cold

08 — Maintenance: What Homeowners Can Do

09 — Humidity, Condensation, and Indoor Air

10 — Energy Use: Practical Ways to Reduce Waste

11 — Repair or Replace? Making a Thoughtful Decision

12 — Choosing a New Air Conditioner or Heat Pump

13 — What Happens During a Professional Service Visit?

14 — Warning Signs: When to Call for Service

15 — Storm Season and Your HVAC Equipment

16 — Indoor Air Quality: What HVAC Can and Cannot Do

17 — Refrigerant: What Homeowners Should Know

18 — Understanding Estimates, Warranties, and Contractors

19 — A Homeowner’s Seasonal HVAC Checklist

20 — Questions to Ask Your HVAC Contractor

Chapter 01: Your Home’s Comfort System: The Big Picture

An air-conditioning system does more than make the air feel cold. A central home comfort system moves air, transfers heat, removes some moisture, filters particles, and responds to the thermostat. Understanding those jobs makes it easier to describe a problem and ask useful questions when a technician visits.

In a typical split central-air system, the indoor equipment contains an evaporator coil and blower. The outdoor unit contains a compressor and condenser coil. Refrigerant circulates through the system and carries heat from indoors to outdoors. The blower moves household air across the indoor coil and sends the conditioned air through supply ducts. Return ducts bring air back to the equipment.

The thermostat is the control, not the cooling system itself. It measures conditions at its location and tells the equipment when to operate. A thermostat in a sunny hallway or near a supply register may not represent how the whole home feels.

The duct system matters just as much as the equipment. Leaky, disconnected, poorly insulated, or restricted ducts can make rooms uncomfortable even when the outdoor unit is running. Airflow depends on properly sized ducts, open registers, clean filters, and a blower operating as designed.

A home may use a heat pump, a straight-cool air conditioner with separate heat, a package unit, or a ductless mini-split. The right maintenance and operating instructions depend on the actual equipment. Find the model and serial numbers, keep the owner’s manuals, and ask a qualified technician to explain the system installed in your home.

A useful first step is to identify the indoor unit, outdoor unit, thermostat, filter location, and main return-air grilles. Do not remove service panels or reach into equipment. Simply knowing where the components are will help you communicate clearly.

Chapter 02: Why Jacksonville Homes Work Hard to Stay Cool

Northeast Florida has long, humid cooling seasons. The air conditioner must manage both temperature and moisture. On a muggy afternoon, the system is not simply removing heat from the house; it is also condensing water vapor from indoor air as warm air passes over the cold evaporator coil.

Humidity can make a room feel warmer than its temperature suggests. It can also contribute to condensation and conditions that support mold growth when moisture is not controlled. The Florida Department of Health advises keeping indoor relative humidity below 60 percent and emphasizes fixing water sources and drying wet materials promptly. The EPA commonly recommends a 30–50 percent indoor range where practical.

A system that is oversized, short-cycles, has poor airflow, or has a control problem may not run long enough to remove moisture effectively. Conversely, a system that runs for long periods during very hot weather is not automatically broken. The home's insulation, windows, ductwork, outdoor temperature, thermostat setting, and equipment capacity all affect run time.

Do not assume that lowering the thermostat several degrees will make the system cool faster. Most central systems cool at their normal operating rate; a much lower setting can simply make the equipment run longer. Set a comfortable target and allow the system time to respond.

Keep windows and exterior doors closed while cooling. Use kitchen and bathroom exhaust fans when needed to remove moisture and odors, and make sure they exhaust outdoors. If the home remains unusually humid, has persistent musty odors, or shows water stains, ask a qualified professional to investigate the source rather than relying on a thermostat adjustment alone.

Chapter 03: How to Choose and Use Your Thermostat

A thermostat tells the heating and cooling equipment when to operate. It does not measure every room, and it cannot compensate for major duct, insulation, equipment, or moisture problems.

Choose a temperature that is comfortable and practical for the household. A programmable or smart thermostat can adjust settings around regular routines, but schedules should reflect how the home is actually used. If you have a heat pump, confirm that the thermostat is configured for that equipment. Incorrect setup can cause poor operation or unnecessary use of auxiliary heat.

Avoid repeatedly changing the setting up and down in an attempt to force faster cooling. Set the target, check that the thermostat is in the correct mode, and give the home time to respond. If the display is blank, check the owner's manual for basic items such as batteries, if the model uses them. Do not remove wiring or open the thermostat base unless you are qualified.

Some thermostats display indoor humidity, filter reminders, equipment alerts, or system run-time information. Treat reminders as prompts to inspect the actual filter and equipment instructions, not as proof that a part has failed. A thermostat's humidity reading may differ from a separate hygrometer.

If one room is consistently warmer than the rest, the answer may not be a new thermostat. Possible causes include sun exposure, insulation differences, duct balancing, closed or blocked registers, air leakage, or equipment capacity. Ask a technician to assess the whole system before purchasing add-on controls.

Keep the thermostat away from direct sunlight, lamps, supply registers, drafts, and heat-producing appliances when its location can be changed by a qualified installer. A thermostat should sense representative indoor conditions.

Chapter 04: Air Filters: A Small Part with a Big Job

The air filter protects HVAC equipment by capturing some airborne particles before they reach sensitive components. A loaded or incorrectly fitted filter can restrict airflow. A filter that is too restrictive for the equipment may also cause airflow problems.

First, locate the filter. It may be in a return-air grille, at the indoor air handler, or in another location specified by the installer. Use the exact size and type recommended by the equipment manufacturer or HVAC professional. Note the airflow arrow on the filter frame and point it in the direction of airflow.

Inspect the filter regularly, especially during heavy-use months, when pets are present, or when construction creates extra dust. Replace or clean it according to the manufacturer's instructions and the conditions in the home. A calendar reminder is helpful, but the correct interval varies. Some filters are disposable; others are washable and must be completely dry before being reinstalled.

MERV is a rating of a filter's ability to capture particles under standardized test conditions. A higher number is not automatically the best choice for every system. Before changing to a higher-efficiency filter, ask whether the blower and filter cabinet can handle it without reducing airflow too much.

Never operate the system without the required filter. Do not stack filters or force an oversized filter into the slot. If the filter bows, leaves gaps, whistles, or is difficult to remove, ask a technician to check the filter rack and airflow.

A filter is not a cure for every indoor-air problem. Source control, moisture control, ventilation, housekeeping, and properly selected filtration all play roles. For unusual dust, odors, or persistent symptoms, investigate the source rather than simply buying a denser filter.

Chapter 05: Outdoor Unit Care and Clear Airflow

The outdoor unit needs room to move air across its coil. Leaves, grass clippings, lint, shrubs, fences, and stored items can obstruct airflow. Keep the area around the unit clear in accordance with the manufacturer's clearance requirements. Do not build a tight enclosure around it or place objects on top.

Homeowners can visually check for obvious debris around the unit when it is safe to do so. Turn off the system at the thermostat before doing simple yard cleanup nearby, and never insert tools, hands, or a hose nozzle through the grille. The fan and electrical components can be dangerous even when the system appears idle.

Do not bend coil fins, remove panels, spray electrical compartments, or use pressure washers or harsh chemicals. Coil cleaning is often best left to a trained technician using methods appropriate for the equipment. If the unit is unusually noisy, vibrates, has visible damage, or repeatedly trips a breaker, stop and arrange professional service.

After mowing, avoid directing grass clippings toward the unit. Keep dryer vents and other exhaust outlets from discharging lint or debris toward the coil. If landscaping is being changed, preserve the required service access and airflow clearance.

The outdoor unit may produce water or condensation in some operating conditions, but standing water, oil-like residue, damaged refrigerant lines, or signs of electrical overheating should be assessed by a professional. Do not touch refrigerant tubing or attempt to add refrigerant. Refrigerant work requires specialized equipment and appropriate certification.

Chapter 06: Ductwork: The Hidden Part of Home Comfort

Ducts carry conditioned air from the air handler to rooms and return air back to the equipment. Because much of the duct system may be in an attic, garage, or crawlspace, problems can go unnoticed.

Leaky or disconnected ducts can waste conditioned air and may draw dusty, hot, or humid air into the system. Poor insulation can allow cooled air to warm up before it reaches a room. Crushed flex duct, closed dampers, blocked returns, and poorly designed transitions can restrict airflow.

Homeowners can look for simple clues without entering unsafe spaces: a room that is persistently uncomfortable, weak airflow at a register, excessive dust, unusual whistling, or a return grille that is blocked by furniture. Keep supply registers and return grilles open and unobstructed unless a technician gives a specific reason otherwise. Closing many registers can upset system airflow and pressure.

Do not crawl into an attic or tight space to inspect ducts if access is unsafe, temperatures are extreme, or there are electrical, structural, or pest hazards. Do not tape or seal ducts with ordinary household duct tape. Proper duct sealing uses materials and methods designed for HVAC systems.

A professional evaluation may include checking accessible duct connections, insulation, static pressure, airflow, and temperature differences. Ask the technician to show you the problem and explain which repairs are necessary. If duct sealing or insulation is recommended, request a description of the affected sections and how the work will be verified.

Chapter 07: Why Some Rooms Are Too Hot or Too Cold

Uneven temperatures are common, but they are not all caused by an undersized air conditioner. A room may receive direct afternoon sun, have older windows, lack insulation, sit above a garage, or be at the far end of a duct run. A closed or blocked register can also reduce comfort.

Start with observations. Note which rooms are affected, what time of day the problem occurs, whether doors are normally open or closed, and whether the problem changes with outdoor weather. Check that supply registers and return grilles are not blocked by rugs, furniture, curtains, or storage.

Avoid closing multiple registers in rooms you do not use. Central systems are designed around a particular airflow path. Closing too many outlets can raise duct pressure and reduce total airflow. If the home has zoning dampers, use the controls as instructed and ask a technician about any persistent imbalance.

Possible solutions include repairing ducts, adjusting balancing dampers, improving insulation or window shading, correcting return-air pathways, or evaluating the equipment and duct design. A booster fan or smart vent is not automatically the right answer; it can sometimes worsen pressure or airflow problems.

Ask for measurements rather than guesses. A technician may compare room temperatures, check supply airflow, inspect duct routing, and evaluate the system's static pressure. If a major replacement is proposed, ask how the contractor determined the capacity needed for the home. A room-by-room load calculation is more meaningful than choosing equipment based only on square footage.

Chapter 08: Maintenance: What Homeowners Can Do

Regular attention helps homeowners notice small problems before they become urgent. The safest routine is simple: check the filter, keep vents clear, keep the outdoor area unobstructed, watch for water, and listen for changes in sound or operation.

Follow the equipment manual for filter care and any homeowner-accessible tasks. If you are unsure where a filter belongs, ask the installer to show you. Keep a record of filter size, model numbers, service dates, and any recurring symptoms.

Look around the indoor air handler for water stains, standing water, rust, or unusual odors. Many systems remove moisture through a condensate drain. If water is appearing where it should not, do not ignore it. A blocked drain, damaged pan, disconnected line, or other fault may be involved. Turn the system off if there is active leaking that could damage the home, and call a qualified technician. Do not pour chemicals into the equipment or drain line unless the manufacturer specifically directs it.

Professional maintenance commonly includes inspecting electrical connections and controls, checking operating temperatures and pressures as appropriate, examining coils and condensate drainage, and confirming airflow and safe operation. The exact checklist should suit the system and manufacturer.

Schedule service before the period when you most depend on cooling, if possible. Keep invoices and ask the technician to distinguish between maintenance observations, recommended repairs, and urgent safety concerns. A maintenance visit is not a guarantee that a component will never fail, but it provides an opportunity to identify developing issues.

Chapter 09: Humidity, Condensation, and Indoor Air

In humid climates, comfort depends on moisture control as well as temperature. Relative humidity describes how much water vapor is in the air compared with the amount the air could hold at that temperature. A room can feel clammy even when the thermostat setting seems reasonable.

The Florida Department of Health advises keeping indoor relative humidity below 60 percent to help prevent mold conditions. The EPA commonly recommends 30–50 percent where practical. These are general indoor-environment recommendations, not a diagnosis or a promise that mold cannot grow.

Use a simple hygrometer to understand indoor conditions over time. Readings can vary by room and device. If humidity remains high, check for obvious moisture sources such as plumbing leaks, roof leaks, wet carpets, unvented bathroom fans, or damp materials. Use kitchen and bathroom exhaust fans that discharge outdoors.

An air conditioner removes moisture while it runs, but it may not control humidity adequately if it is oversized, short-cycling, poorly maintained, or affected by airflow or drainage problems. A separate dehumidifier may be appropriate in some homes, but it adds heat to the space and requires correct drainage and maintenance. Ask a qualified professional to

investigate persistent high humidity before buying equipment.

If you see visible mold, water stains, or recurring musty odors, address the moisture source. Do not assume that spraying fragrance or painting over a stain solves the problem. Large areas, recurring growth, contaminated materials, or suspected HVAC-system contamination call for qualified help. The Florida Department of Health and EPA provide guidance on moisture and mold.

Chapter 10: Energy Use: Practical Ways to Reduce Waste

Heating and cooling can be a major part of household energy use, especially in a long cooling season. The most useful first steps are often ordinary: keep the filter maintained, seal obvious air leaks, use window coverings to reduce unwanted solar heat, and make sure ducts are in good condition.

A programmable thermostat can reduce unnecessary heating or cooling when the home is unoccupied, provided the schedule suits the equipment and household. Avoid extreme setbacks that make the system struggle to recover or cause discomfort. Heat-pump systems may need specific thermostat settings; follow the equipment instructions.

Ceiling fans can improve comfort by moving air across occupants. Fans cool people, not empty rooms, so switch them off when no one is there. Set fan direction according to the fan manufacturer's instructions and season.

Air sealing and insulation can help reduce heat entering the home. Pay attention to attic insulation, attic access panels, weatherstripping, door sweeps, and gaps around plumbing or wiring penetrations. Do not block required combustion-air openings or ventilation pathways. If you are considering insulation or air sealing, use a qualified contractor familiar with building science and local code.

When comparing replacement equipment, look beyond a single efficiency number. Ask about the complete installed system, sizing, duct compatibility, controls, warranty, and expected operating conditions. Efficiency ratings are useful for comparing products under standardized conditions, but actual bills depend on weather, home construction, thermostat settings, occupancy, and installation quality.

Chapter 11: Repair or Replace? Making a Thoughtful Decision

A breakdown does not automatically mean the entire system must be replaced. Some problems are relatively limited; others involve major components, obsolete refrigerant, repeated failures, severe corrosion, or equipment that no longer meets the home's needs.

Before deciding, ask the contractor to explain the diagnosis, the failed component, the proposed repair, and any alternatives. Request an itemized estimate. If replacement is recommended, ask why repair is not a reasonable option and whether the existing ductwork, electrical service, drain arrangement, and equipment location are suitable for new equipment.

Consider the system's age, repair history, reliability, comfort, energy use, refrigerant type, parts availability, warranty, and the cost of the proposed repair compared with replacement. There is no single age or dollar threshold that applies to every home.

A new system should be selected for the house, not simply as a larger version of the old one. Ask how the contractor calculated heating and cooling loads, evaluated ducts, and selected equipment capacity. Oversizing can contribute to short run cycles and poor humidity removal; undersizing can leave the home uncomfortable during demanding weather.

Get more than one written proposal for a major replacement when practical. Compare the scope, model numbers, efficiency ratings, included accessories, permits, labor, warranty, and commissioning—not just the bottom-line price. A

careful installation is essential to the performance of the equipment.

Chapter 12: Choosing a New Air Conditioner or Heat Pump

A replacement system is a long-term home investment. The right choice depends on the home's heating and cooling loads, duct system, electrical service, budget, comfort goals, and local climate.

A heat pump moves heat rather than creating it through electric resistance. In cooling mode it operates much like an air conditioner; in heating mode it reverses the refrigerant cycle to bring heat indoors. Some homes use a heat pump with supplemental heat. Other homes use a straight-cool air conditioner with a separate heating system.

Efficiency labels and ratings can help compare equipment, but ask the contractor to explain what the rating means for the specific model and system combination. Confirm that the quoted indoor and outdoor components are approved to operate together.

Proper sizing is critical. Ask whether the contractor performed a recognized heating and cooling load calculation using the home's construction, insulation, windows, orientation, occupancy assumptions, and local design conditions. A rule of thumb based only on square footage is not a substitute for a load calculation.

The proposal should identify model numbers, capacity, efficiency ratings, thermostat, filter arrangement, condensate management, duct modifications, electrical work, permits, start-up and commissioning, warranty terms, and disposal of old equipment. Ask who will obtain permits and who is responsible for inspections.

Do not select equipment solely because it has the highest advertised efficiency or the largest capacity. A good system is properly matched, correctly sized, installed to manufacturer requirements, and tested before the contractor leaves.

Chapter 13: What Happens During a Professional Service Visit?

A good service visit should begin with listening. Tell the technician what you noticed, when it happens, what settings you use, and whether the issue is constant or intermittent. Mention unusual sounds, odors, water, breaker trips, or rooms that do not feel comfortable.

The technician may inspect the thermostat, filter, indoor and outdoor equipment, electrical components, condensate drainage, refrigerant circuit, ductwork, and airflow. The exact checks depend on the complaint and equipment. Some measurements require the system to operate under suitable conditions.

Ask the technician to explain findings in plain language. If a part is recommended for replacement, ask what it does, how it failed, and whether the system can be operated safely while you consider the estimate. Request photographs or measurements when they help clarify the issue.

A technician should not needlessly pressure you into an immediate major purchase. For a costly repair or full replacement, a written estimate and second opinion may be sensible unless there is an immediate safety concern.

Before the technician leaves, ask what was completed, what remains to be monitored, whether any maintenance is due, and what warning signs should prompt another call. Keep the invoice with your equipment records. Clear communication helps both the homeowner and service company.

Chapter 14: Warning Signs: When to Call for Service

Some symptoms can be checked safely; others require prompt professional attention. If the system runs but the home does not cool, first confirm the thermostat is set to cooling, the temperature setting is below the current room temperature, and the filter and visible supply/return grilles are not blocked. If these simple checks do not explain the problem, arrange service.

Call a technician if you notice weak airflow, repeated icing, water leaking from the indoor unit, persistent musty odors, unusual grinding or buzzing, frequent cycling, a sudden unexplained increase in energy use, or a system that repeatedly shuts down.

If you see smoke, sparks, burning electrical odors, or a damaged electrical component, keep clear and seek appropriate emergency or electrical assistance. Do not open equipment panels. If a breaker trips repeatedly, do not keep resetting it; repeated trips indicate a fault that needs diagnosis.

If refrigerant lines or coils appear damaged, do not touch them. Refrigerant can cause injury, and repairs require specialized equipment and appropriate certification. Do not attempt to locate leaks with a flame or add refrigerant from a consumer kit.

If water is actively damaging ceilings, walls, or floors, shut the system off if you can do so safely and contact a professional. Protect people and property first. Never enter standing water around electrical equipment.

Chapter 15: Storm Season and Your HVAC Equipment

Northeast Florida homeowners should include HVAC equipment in their storm preparations. Before hurricane season, know where the system disconnect and main electrical panel are, but only operate them if conditions are safe and you understand the equipment. Do not approach damaged wires, flooded equipment, or a wet electrical panel.

Secure loose outdoor items that could become projectiles. Do not wrap or cover an outdoor unit in a way that traps moisture or blocks ventilation during normal operation. Follow the equipment manufacturer's instructions for any storm protection.

If flooding, storm surge, or debris reaches the equipment, do not turn it on until it has been inspected by a qualified professional. Water can damage electrical components and contaminate equipment. Do not assume that an outdoor unit is safe simply because the water has receded.

After a storm, look from a safe distance for shifted equipment, damaged refrigerant lines, fallen branches, debris, exposed wiring, or water around the indoor air handler. Photograph visible damage for records if it is safe to do so. Contact your insurer and qualified contractors as appropriate.

If power is interrupted, follow utility and emergency-management instructions. Once power returns, avoid repeatedly cycling the system if it does not start normally. Some equipment has time delays or protective controls; consult the manual and call for help if operation is abnormal.

Chapter 16: Indoor Air Quality: What HVAC Can and Cannot Do

Heating and cooling equipment can support indoor air quality through filtration, ventilation, and moisture control, but no single filter or add-on device solves every indoor-air concern.

Begin with source control. Avoid indoor smoking, use kitchen and bathroom exhaust fans, store chemicals as directed, and fix leaks and dampness. Ventilation can dilute some indoor pollutants, but outdoor air may also bring humidity, pollen, smoke, or other contaminants. Ventilation should be appropriate for the home and climate.

Filtration can capture particles when the filter is correctly selected, installed, and maintained. Ask a qualified HVAC professional which filter efficiency is compatible with your equipment. A filter that is too restrictive may reduce airflow. Portable air cleaners may help in particular rooms when appropriately sized and maintained.

Be cautious about products marketed with sweeping claims such as eliminating all allergens, viruses, odors, or mold. Ask what the device actually removes, what independent testing supports the claim, what byproducts may be produced, and what maintenance is required. The EPA advises focusing on source control, ventilation, and filtration as complementary strategies.

If household members have persistent health symptoms, consult a healthcare professional. An HVAC contractor can evaluate equipment and building conditions but should not diagnose medical problems. For radon, carbon monoxide, mold, or other specific hazards, use the appropriate testing and qualified professionals.

Chapter 17: Refrigerant: What Homeowners Should Know

Refrigerant is the working fluid that moves heat through an air-conditioning or heat-pump system. It circulates in a sealed circuit and changes pressure and state as it moves through the compressor, coils, and expansion device.

Homeowners do not need to handle refrigerant. Refrigerant service requires specialized tools, training, and compliance with applicable environmental rules. Never loosen refrigerant fittings, cut tubing, attempt a do-it-yourself recharge, or release refrigerant into the atmosphere.

If a system is low on refrigerant, the important question is why. A properly operating sealed system should not routinely need refrigerant added. A qualified technician should investigate possible leaks, explain the findings, and discuss repair options.

Different systems use different refrigerants. When replacing equipment, ask which refrigerant the proposed system uses, whether it is compatible with the indoor and outdoor components, and what the long-term service implications are. Do not assume that refrigerants can be mixed or substituted.

If you see oily residue around a refrigerant connection or suspect physical damage, keep clear and arrange professional inspection. Do not touch frost-covered tubing or attempt to thaw an iced coil with tools or hot water. Turn the system off if instructed by the manufacturer or technician and seek service.

Chapter 18: Understanding Estimates, Warranties, and Contractors

A written estimate should make it clear what work is included and what is not. For a repair, look for the diagnostic findings, parts, labor, any trip or diagnostic charge, and warranty on the work. For a replacement, look for equipment model numbers, capacity, efficiency ratings, accessories, duct or electrical work, permits, start-up, commissioning, cleanup, and disposal.

Ask who will perform the work and who is responsible for permits and inspections. Verify the contractor's applicable Florida license and insurance before authorizing significant work. Florida's Department of Business and Professional Regulation provides license information and verification resources.

Read warranty terms carefully. Manufacturer parts coverage may have registration requirements and may not include labor. A contractor's labor warranty is separate. Ask what could void coverage, who handles claims, and whether maintenance records are required.

Be cautious of high-pressure sales tactics, vague equipment descriptions, unusually large deposits, or claims that a repair must be approved immediately when no safety emergency exists. Get the proposal in writing and keep copies of payments,

permits, model numbers, and service records.

A low price is not always the best value, and a high price does not guarantee quality. Compare the work scope and the contractor's explanation. A trustworthy professional should be willing to answer reasonable questions.

Chapter 19: A Homeowner’s Seasonal HVAC Checklist

Use this checklist as a reminder, not a substitute for your equipment manual or professional maintenance.

Monthly or as conditions require: • Inspect the filter and replace or clean it according to the manufacturer's instructions. • Keep supply registers and return grilles unobstructed. • Notice changes in sound, airflow, odor, run time, or comfort. • Check accessible areas around the indoor unit for signs of water.

During the cooling season: • Keep the outdoor unit clear of leaves, grass, and stored items. • Use bathroom and kitchen exhaust fans when producing moisture. • Keep doors and windows closed while cooling. • Watch indoor humidity and investigate persistent dampness or musty odors.

Before the hottest months: • Arrange a professional inspection if one is due or if the system has shown warning signs. • Confirm that you know the filter size and location. • Review thermostat schedules and make sure settings match the equipment. • Clear the service area around the outdoor unit.

Before and after severe storms: • Secure loose yard items. • Follow official storm and utility instructions. • Do not operate flooded or visibly damaged equipment until it has been inspected. • Keep clear of fallen wires and damaged electrical components.

Keep a simple log with service dates, filter changes, symptoms, repairs, and equipment model numbers. This record helps identify patterns and gives a technician useful background.

Chapter 20: Questions to Ask Your HVAC Contractor

Good questions lead to clearer decisions. You do not need to know every technical term; you need to understand what is being recommended and why.

For a service call: • What did you find, and what measurements support the diagnosis? • Is the system safe to operate? • What repair is necessary now, and what can be monitored? • Can you show me the affected component? • What is included in the price and warranty?

For a replacement: • How did you calculate the home's heating and cooling load? • Is the existing duct system suitable for the new equipment? • What are the exact indoor and outdoor model numbers? • What efficiency ratings apply to this matched system? • Are permits, inspections, electrical changes, drain work, and duct modifications included? • Who will start up and commission the system? • What are the manufacturer parts and contractor labor warranties?

For maintenance: • What tasks did you perform? • Were any measurements outside the manufacturer's specifications? • Are there developing issues I should plan for? • What filter type and replacement interval does this system require?

Ask for answers in writing when they affect price, scope, or safety. A good contractor should welcome informed questions and explain the work without making you feel foolish. The goal is not to become an HVAC technician. It is to understand your home, recognize warning signs, and make confident decisions with qualified help.

Sources & Further Reading

Selected government and technical resources used to check general homeowner guidance:

• U.S. Department of Energy — Consumer Guide to Home Heating and Cooling
https://www.energy.gov/energysaver/heat-and-cool

• U.S. Department of Energy — Home Cooling Systems
https://www.energy.gov/energysaver/home-cooling-systems

• U.S. Environmental Protection Agency — Care for Your Air: A Guide to Indoor Air Quality
https://www.epa.gov/indoor-air-quality-iaq/care-your-air-guide-indoor-air-quality

• U.S. Environmental Protection Agency — What Can I Do to Improve Indoor Air Quality in My Home?
https://www.epa.gov/indoor-air-quality-iaq/what-can-i-do-improve-indoor-air-quality-my-home

• Florida Department of Health — Mold
https://www.floridahealth.gov/community-environmental-public-health/environmental-public-health/air-quality/mold/

• U.S. Department of Energy — HVAC Proper Installation of Filters
https://bsesc.energy.gov/energy-basics/hvac-proper-installation-filters

• Florida Department of Business and Professional Regulation — Verify a License
https://www.myfloridalicense.com/wl11.asp

Publication note: This is a fictional demonstration publication. A real customer edition should be customized with verified business information and reviewed by a qualified HVAC professional before publication.